

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Combustible.

Supplemental information

80.88% of the mixture consists of component(s) of unknown acute dermal toxicity. 61.8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 58.87% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Stoddard Solvent		8052-41-3	60 - < 70
Low Odor Base Solvent		64742-47-8	10 - < 20
1000 cSt Silicone		63148-62-9	5 - < 10
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	5 - < 10
Carbon Dioxide		124-38-9	3 - < 5
Trimethylbenzene		25551-13-7	3 - < 5
ETHYLBENZENE		100-41-4	1 - < 3
BENZENE,1-METHYLETHYL-		98-82-8	< 1
Other components below reportable levels			1 - < 3

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol. Combustible.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	PEL	245 mg/m3	
Carbon Dioxide (CAS 124-38-9)	PEL	50 ppm 9000 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	5000 ppm 5 mg/m3	Mist.
ETHYLBENZENE (CAS 100-41-4)	PEL	2000 mg/m3 500 ppm 435 mg/m3	
Stoddard Solvent (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	TWA	50 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA TWA	5000 ppm 5 mg/m3	Inhalable fraction.
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	TWA	245 mg/m3	
Carbon Dioxide (CAS 124-38-9)	STEL	50 ppm 54000 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	30000 ppm 9000 mg/m3 5000 ppm 1800 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	Ceiling		
	STEL	10 mg/m3	Mist.
	STEL	545 mg/m3	
	TWA	125 ppm 435 mg/m3 100 ppm	
Low Odor Base Solvent (CAS 64742-47-8)	TWA	100 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear. Liquid.
Physical state	Liquid.
Form	Aerosol.
Color	Pale yellow
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-94 °F (-70 °C) estimated
Initial boiling point and boiling range	302 °F (150 °C) estimated
Flash point	117.0 °F (47.2 °C)
Evaporation rate	Not available.

Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.7 % estimated
Flammability limit - upper (%)	6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	1.72 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	410 °F (210 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	6.80 lbs/gal
Explosive properties	Not explosive.
Flame extension	25 in
Flammability (flash back)	No
Flammability class	Combustible II estimated
Heat of combustion (NFPA 30B)	29.06 kJ/g estimated
Moisture	< 0.03 %
Oxidizing properties	Not oxidizing.
Percent volatile	1.64 % estimated
Specific gravity	0.82
VOC (Weight %)	58.5 % w/w

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.
---	---

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed. Narcotic effects.

Components **Species** **Test Results**

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Acute

Inhalation

LC50	Mouse	2000 ppm, 7 Hours 24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours

Oral

LD50	Rat	1400 mg/kg
------	-----	------------

ETHYLBENZENE (CAS 100-41-4)

Acute

Dermal

LD50	Rabbit	17800 mg/kg
------	--------	-------------

Oral

LD50	Rat	3500 mg/kg
------	-----	------------

Trimethylbenzene (CAS 25551-13-7)

Acute

Oral

LD50	Rat	8970 mg/kg
------	-----	------------

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	2B Possibly carcinogenic to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Stoddard Solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Known To Be Human Carcinogen.
---	-------------------------------

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1000 cSt Silicone (CAS 63148-62-9)		
Aquatic		
Fish	LC50	Channel catfish (<i>Ictalurus punctatus</i>) 2.36 - 4.15 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.7 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.5 - 11 mg/l, 96 hours
Low Odor Base Solvent (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE,1-METHYLETHYL-	3.66
ETHYLBENZENE	3.15
Stoddard Solvent	3.16 - 7.15

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer Commodity
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Label(s)	3
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202

Packaging bulk 242

IATA

UN number UN1950

UN proper shipping name Aerosol, flammable

Transport hazard class(es)

Class 2

Subsidiary risk -

Packing group Not applicable.

Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Forbidden.

Cargo aircraft only Forbidden.

IMDG

UN number UN1950

UN proper shipping name Aerosols

Transport hazard class(es)

Class 2

Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Listed.

ETHYLBENZENE (CAS 100-41-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
ETHYLBENZENE	100-41-4	1 - < 3
BENZENE,1-METHYLETHYL-	98-82-8	< 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 ETHYLBENZENE (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)
 ETHYLBENZENE (CAS 100-41-4)
 Low Odor Base Solvent (CAS 64742-47-8)
 Stoddard Solvent (CAS 8052-41-3)
 Trimethylbenzene (CAS 25551-13-7)

US. Massachusetts RTK - Substance List

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Carbon Dioxide (CAS 124-38-9)
 Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)
 ETHYLBENZENE (CAS 100-41-4)
 Low Odor Base Solvent (CAS 64742-47-8)
 Stoddard Solvent (CAS 8052-41-3)
 Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Carbon Dioxide (CAS 124-38-9)
 ETHYLBENZENE (CAS 100-41-4)
 Low Odor Base Solvent (CAS 64742-47-8)
 Stoddard Solvent (CAS 8052-41-3)
 Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 Carbon Dioxide (CAS 124-38-9)
 ETHYLBENZENE (CAS 100-41-4)
 Low Odor Base Solvent (CAS 64742-47-8)
 Stoddard Solvent (CAS 8052-41-3)
 Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 ETHYLBENZENE (CAS 100-41-4)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Listed: April 6, 2010
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-01-2015

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product Uses
Composition / Information on Ingredients: Ingredients
Transport Information: Material Transportation Information
Regulatory Information: TSCA 12b Exported Products
HazReg Data: International Inventories
GHS: Classification