

Material Safety Data Sheet This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS CLASS E: Corrosive liquid.

.HCS CLASS: Corrosive liquid.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Chemical Product and Company Identification			
Product Name/ Trade name	Ultra 2000	Code	136
Synonym	Super Double Strength Degreaser	CAS#	Not applicable.
Chemical Family	Not available.	Validation Date	3/20/2004
Chemical Formula	Not applicable.	Print Date	3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	nemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	<u>ا</u>	Protective Clothing

Name	CAS#	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
1) 2-Butoxyethanol	111-76-2	5-10	TWA: 20 (ppm) from ACGIH (TLV) [United States] TWA: 50 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 1746 mg/kg [Rat].
Potassium Metasilicate Sodium Metasilicate Sodium Xylene Sulfonate	1312-76-1 6834-92-0 1300-72-7	5-10 1-5 5-10	Not available. Not available. Not available.	Not available. Not available. ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse].
5) Potassium Hydroxide6) Anionic Surfactant7) Nonionic Surfactant	1310-58-3 25155-30-0 9016-45-9	0-5 0-5 <2	Not available. Not available. Not available.	Not available. Not available. Not available. Not available.

Section 3. Hazards Id	lentification
Potential Acute Health Effects	Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.
Potential Chronic Health Effects	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce nervous system damage.
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First	t Aid Measures
Eye Contact	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
Skin Contact	Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

Section 5. Fire Fight	Section 5. Fire Fighting Measures	
Products of Combustion	Not available.	
Fire Fighting Media and Instructions	Non-flammable substance.	
Special Remarks on Fire Hazards	No additional remark.	
Special Remarks on Explosion Hazards	No additional remark.	

Section 6. Accidental Release Measures	
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage		
Precautions	After handling, always wash hands thoroughly with soap and water. Avoid contact with skin and eyes.	
Incompatibility	Strong acids. acids	
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of reach of children. For Institutional and Commercial Use	

Section 8. Exposure (Controls/Personal Protection
Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection Eyes	Splash goggles.
Body	Long Pants and Long Sleeves to avoid skin cotact. No additional special protective clothing is required.
Respiratory	Wear appropriate respirator when ventilation is inadequate.
Hands	Gloves (impervious).
Protective Clothing (Pictograms)	

Exposure Limits

2-Butoxyethanol TWA: 25 (ppm) TWA: 50 (ppm) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physical a	and Chemical Properties		
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	Not available.
рН	13.0 - 13.9 [Basic.]	Color	Green.
Boiling/Condensation Point	215°F initial		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.08 (Water = 1)		
Vapor Pressure	20mm Hg @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	80		
voc	Not available.		
Evaporation Rate	<1 compared to Water		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: >98.889°C (210°F).		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	No specific information is available in our opresence of various materials.	database i	regarding the flammability of this product in
Explosion Hazards in Presence of Various Substances	Not applicable		

Section 10. Stability and Reactivity Data	
Stability	The product is stable.
Incompatibility with Various Substances	Strong acids. acids
Hazardous Decomposition Products	Not available.

Section 11. Toxicolog	gical Information
Routes of Entry	Eye Contact Ingestion. INHALATION Skin contact.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.
	Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).
Acute Effects on Humans	
Eyes	Corrosive to skin and eyes on contact. Eye contact can result in corneal damage .
Skin	Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Inhalation	Harmful if inhaled.
Ingestion	Irritating to mouth, throat and stomach. May cause headache, dizziness, nausea, vomiting and diarrhea.
Chronic Effects on Humans	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce nervous system damage.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.

Section 12. Ecological Information		
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.	
Toxicity of the Products of Biodegradation	Not available.	
Special Remarks on the Products of Biodegradation	No additional remark.	

Section 13. Disposal Considerations			
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.		
Waste Stream	Not available.		

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification 8



PIN UN, Proper Shipping Name, PG Shipping name: Corrosive liquids n.o.s. UNNA: 1760 PG: II

Maritime Transportation Not available. **Special Provisions for** Not available. Transport

NATIONALE (CITATION CONTRACTOR CO	WHMIS CLASS E: Corr	onivo liquid		
WHMIS (Classification)	WHIMIS CLASS E: CON	osive ilquia.		
Regulatory Lists	SARA 313; 2-Butoxyethanol			
Other Regulations	OSHA: Hazardous	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).		
Other Classifications	HCS (U.S.A.)	.HCS CLASS: Corrosive liquid.		
	USA Regulatory Lists	California prop. 65: This product contains the following ingredients for w State of California has found to cause reproductive harm (female) which require a warning under the statute: Ethylene Oxide < 1ppm California prop. 65: This product contains the following ingredients for w State of California has found to cause cancer which would require a war the statute: Ethylene Oxide <1 ppm Massachusetts RTK: Ethylene Oxide		
		SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard; Potassium Hydroxide: immediate health hazard SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol		
	DSD (EEC)	R35- Causes severe burns.		
International No products were found. Regulations Lists				
Hazardous Material Information System (U.S.A.)	Health Flammability Physical Hazard	* 3 National Fire Protection Association (U.S.A.)	Health 3	

Section 16. Other Information					
Validated by CRushton on 3/20/2004.		Verified by CRushton.			
		Printed 3/27/2004.			
Information Contact	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607				

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/20/2004.	Ultra 2000	Page: 6/6

Continued on Next Page