

## Material Safety Data Sheet This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

		WHMIS CLASS E: Corrosive liquid.	.HCS	CLASS	5: Corrosive liquid.
WHMIS (Pictogra	ms)	WHMIS (Classification)			HCS
Section 1. Che	emica	l Product and Company Identification			
Product Name/ Trade name	Ultr	a 2000	Code		136
Synonym	Super	Double Strength Degreaser	CAS #		Not applicable.
Chemical Family	Not av	vailable.	Validatio	n Date	1/23/2008
Chemical Formula	Not a	oplicable.	Print Dat	e	1/23/2008
Manufacturer/ Supplier	1001 Toled	Corporation Brown Avenue o, Oh 43607 241-2156	<u>In Case of</u> <u>Emergency</u>	Che	emtrec (800) 424-9300
TSCA	TSCA	Inventory: All components listed or are exempt from listing.			
DSL/ NDSL	All cor	nponents listed unless noted elsewhere on this MSDS		Pro	tective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS #	% by Weight	Exposure Limits	LC <sub>50</sub> /LD <sub>50</sub>
2-Butoxyethanol	111-76-2	5 - 10	ACGIH (United States). TWA: 20 ppm OSHA (United States). TWA: 50 ppm	ORAL (LD50): Acute: 1746 mg/kg [Rat].
Sodium Metasilicate	6834-92-0	1 - 5	Not available.	Not available.
Sodium Hydroxide	1310-73-2	1 - 5	<b>OSHA (United States).</b> TWA: 2 mg/m <sup>3</sup>	ORAL (LD50): Acute: 140 mg/kg [Rat].
Sodium Xylene Sulfonate	1300-72-7	1 - 5	Not available.	ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse].
Dodecylbenzene Sulfonic Acid (DDBSA)	27176-87-0	1 - 5	Not available.	Not available.

Section 3. Hazard	s Identification
Potential Acute Health Effects	Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.
Potential Chronic Health Effects	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance nervous system damage.
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. Fir	st Aid Measures
Eye Contact	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
Skin Contact	Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

Section 5. Fire Fighting Measures		
Products of Combustion	Not available.	
Fire Fighting Media and Instructions	Non-flammable substance.	
Special Remarks on Fire Hazards	No additional remark.	
Special Remarks on Explosion Hazards	No additional remark.	

Section 6. Accide	ental Release Measures
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage		
Precautions	After handling, always wash hands thoroughly with soap and water. Avoid contact with skin and eyes.	
Incompatibility	Strong acids. acids	
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of reach of children. For Institutional and Commercial Use	

re Controls/Personal Protection
Good general ventilation should be sufficient to control airborne levels.
Splash goggles.
Long Pants and Long Sleeves to avoid skin cotact. No additional special protective clothing is required.
Wear appropriate respirator when ventilation is inadequate.
Gloves (impervious).
,

**Exposure Limits** 

**2-Butoxyethanol** TWA: 25 (ppm) TWA: 50 (ppm) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physica	al and Chemical Properties		
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	Not available.
рН	12.5 to 13.5 [Basic.]	Color	Green.
Boiling/Condensation Point	215°F initial		
<b>Melting/Freezing Point</b>	Not available.		
<b>Critical Temperature</b>	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.04858 (Water = 1)		
Vapor Pressure	20mm Hg @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	80		
VOC	Not available.		
<b>Evaporation Rate</b>	<1 compared to Water		
<b>Dispersion Properties</b>	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: >98.889°C (210°F).		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	No specific information is available in our in presence of various materials.	database	e regarding the flammability of this product
Explosion Hazards in Presence of Various Substances	Not applicable		

Section 10. Stabili	Section 10. Stability and Reactivity Data	
Stability	The product is stable.	
Incompatibility with Various Substances	Strong acids. acids	
Hazardous Decomposition Not available. Products		

Section 11. Toxico	ological Information
<b>Routes of Entry</b>	Eye Contact Ingestion. INHALATION Skin contact.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).
Acute Effects on Humans	
Eyes	Corrosive to skin and eyes on contact. Eye contact can result in corneal damage .
Skin	Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Inhalation	Harmful if inhaled.
Ingestion	Irritating to mouth, throat and stomach. May cause headache, dizziness, nausea, vomiting and diarrhea.
Chronic Effects on Humans	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce liver damage.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.

Section 12. Ecological Information			
Ecotoxicity	Not available.		
BOD5 and COD	Not available.		
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.		
Toxicity of the Products o Biodegradation	f Not available.		
Special Remarks on the Products of Biodegradation	No additional remark.		

Section 13. Disposal Considerations		
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
Waste Stream	Not available.	

Section 14. Transport Information						
DOT (U.S.A) (Pictograms)	CORROSIVE					
TDG Classification	8					

PIN UN, Proper Shipping Shipping name: Corrosive liquids n.o.s. UNNA: 1760 PG: II Name, PG

Maritime Transportation Not available.

Special Provisions for Not available. Transport

WHMIS (Classification)	WHMIS CLASS E: Corrosive liquid.		
Regulatory Lists	SARA 313; 2-Butoxyethanol		
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).		
Other Classifications	HCS (U.S.A.)	.HCS CLASS: Corrosive liquid.	
	USA Regulatory Lists	California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxide < 1ppm California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide <1 ppm Massachusetts RTK: Ethylene Oxide SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard; SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol	
	DSD (EEC)	R35- Causes severe burns.	
	International Regulations Lists	No products were found.	
Hazardous Material Information System (U.S.A.)	Health Flammability Physical Hazard	<ul> <li>* 3 National Fire</li> <li>0 Protection</li> <li>0 Association</li> <li>(U.S.A.)</li> </ul>	
		rovide only a quick reference for hazard information. The ENTIRE Specific Hazard ards, First Aid measures, and PPE associated with this product.	

## Section 16. Other Information

Validated by CRushton on 1/23/2008.

Verified by CRushton. Printed 1/23/2008.

Information Contact Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607

Notice to Reade

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Continued on Next Page